Material Safety Data Sheet

Date of Preparation: 07/02/98

GEAR FILM

Section 1 - Chemical Product and Company Identification

Product/Chemical Name: GEAR FILM Chemical Formula: CAS Number:

Other Designations:

General Use:

Manufacturer: MIRANDY PRODUCTS, LLC., 1078 GRAND AVENUE, S. HEMPSTEAD, NY 11550

(516) 489-6800

☆☆☆☆☆ Emergency Overview ☆☆☆☆☆

Section 2 - Composition / Information on Ingredients					
Ingredient Name	CAS Number	% wt <i>or</i> % vol			
Isoparaffinic Hyrdocarbon	64741-66-8	10-20			
Propylene Glycol Monomethyl Ether	107-98-2	05-10			
Liquified Petroleum Gas	68476-85-7	40-60			

Trace Impurities:

	OSHA PEL		ACGIH TLV		NIOSH REL		NIOSH	
Ingredient	TWA	STEL	TWA	STEL	TWA	STEL	IDLH	
Isoparaffinic Hyrdocarbon	400 ppm	400 ppm	400 ppm	400 ppm	none estab.	none estab.	none estab.	
Propylene Glycol Monomethyl Ether	100 ppm	100 ppm	100 ppm	100 ppm	none estab.	none estab.	none estab.	
Liquified Petroleum Gas	1000 ppm	1000 ppm	1000 ppm	1000 ppm	none estab.	none estab.	none estab.	

Toxicity Data:

Section 3 - Physical and Chemical Properties

Physical State:

Appearance and Odor: Black, viscous, tacky liquid, solvent odor Vapor Pressure: 55 Vapor Density (Air=1): >1 Formula Weight: Density: Specific Gravity (H₂O=1, at 4 °C): 0.855 pH: N/A Water Solubility: Slight Other Solubilities: Boiling Point: 160F Freezing/Melting Point: Viscosity: Refractive Index: Surface Tension: % Volatile: 68% Evaporation Rate:
 HMIS

 H
 1

 F
 3

 R
 0

 PPE B

GEAR FILM Section 4 - Fire-Fighting Measures

revision_date: 03/09/09

NFPA

Flash Point: 40F Flash Point Method: Burning Pate:

Burning Rate: Autoignition Temperature:

LEL:

UEL:

Flammability Classification: Extremely Flammable spray

Extinguishing Media: Foam, CO2, Dry Media

Unusual Fire or Explosion Hazards: Exposure to temperatures above 120F may cause bursting.

Hazardous Combustion Products:

Fire-Fighting Instructions: Cool fire exposed containers to prevent rupturing.

Fire-Fighting Equipment: Because fire may produce toxic thermal decomposition products, wear a self-contained breathing apparatus (SCBA) and protective clothing.

Section 5 - Stability and Reactivity

Stability: Stable

Polymerization: Hazardous polymerization cannot occur.

Chemical Incompatibilities: Avoid contact with strong oxidizing agents.

Conditions to Avoid:

Hazardous Decomposition Products: Carbon Dioxide, Carbon Monoxide

Section 6 - Health Hazard Information

Potential Health Effects

Primary Entry Routes: Target Organs:

Acute Effects

Inhalation: Inhalation of mist can cause irritation of nasal and respiratory passages; abusive and excessive inhalation may cause irritation to the upper respiratory tract, dizziness, nausea and other central nervous system effects.

Eye: May cause slight irritation but does not injure eye tissue.

Skin: Frequent or prolonged contact may cause irritation.

Ingestion: Can cause severe gastrointestinal irritation, nausea, vomiting and diarrhea.

Carcinogenicity: Not listed.

Medical Conditions Aggravated by Long-Term Exposure:

Chronic Effects:

Emergency and First Aid Procedures

Inhalation: Remove to fresh air. Seek medical attention immediately. If breathing stops, give artificial respiration. **Eye Contact:** Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists get medical attention immediately.

Skin Contact: Wash with soap and water. If irritation persists, seek medical attention.

Ingestion: Do not induce vomiting. Seek medical attention immediately.

After first aid, get appropriate in-plant, paramedic, or community medical support.

Note to Physicians:

Special Precautions/Procedures:

Section 7 - Spill, Leak, and Disposal Procedures

Spill /Leak Procedures: Allow propellant to evaporate. Maintain local exhaust and adequate ventilation. No smoking. Keep sparks; heat sources and open flame far away from spill or leak.

Small Spills:

Large Spills

Containment:

Cleanup: Cover with absorbent material and sweep up. Wash area to prevent slipping.

Regulatory Requirements: Follow applicable OSHA regulations (29 CFR 1910.120).

Disposal: Follow applicable Federal, state, and local regulations.

Disposal Regulatory Requirements:

Container Cleaning and Disposal: Aerosol cans, when emptied and depressurized through normal use, pose no disposal hazard and should be recycled. Consult federal, state and local authorities for approved procedures. **Ecological Information:**

GEAR FILM

Section 8 - Exposure Controls / Personal Protection

Engineering Controls:

Ventilation: Provide general or local exhaust ventilation systems to maintain airborne concentrations below OSHA PELs (Sec. 2). Local exhaust ventilation is preferred because it prevents contaminant dispersion into the work area by controlling it at its source.

Administrative Controls:

Respiratory Protection: None needed for proper use in accordance with label directions.

Protective Clothing/Equipment: Wear chemically protective gloves if repeated skin contact. Wear protective eyeglasses or chemical safety goggles if a splash or spray back may occur.

Safety Stations:

Contaminated Equipment: Separate contaminated work clothes from street clothes. Launder before reuse.

Comments: Never eat, drink, or smoke in work areas. Practice good personal hygiene after using this material, especially before eating, drinking, smoking, using the toilet, or applying cosmetics.

Section 9 - Special Precautions and Comments

Handling Precautions:

Storage Requirements: Keep out of reach of children. For industrial and institutional use only. Store in a cool, dry area, away from heat an open flame. Do not store at temperatures above 120F.

Disclaimer: The information contained on this MSDS is considered accurate as of the date of publication. The suggestions should not be confused with, nor followed in violation of applicable laws, regulations, rules or insurance requirements. No warranty, express or implied, of merchantability, fitness, accuracy of data, or the results to be obtained from the use thereof is made. The vendor assumes no responsibility for injury or damages resulting from the inappropriate use of this product.